

SHEET RUBBER PRODUCTS CATALOG



BUCHANAN RUBBER LTD.

CONDITIONS OF SALE

RETURNS

Merchandise may not be returned without authorization. Approved return must be prepaid and are subject to a 15% restocking charge.

CONDITION OF SALE

The purchaser agrees to the following provisions:

- a) "The seller shall not be liable in damages for, nor deemed to be in default by reason of any failure or delay in shipment of all or any part of this order caused by war, fire, flood, strikes, lockouts, accidents, Act of God, Government order or requirement, interruption or shortage of materials or transportation facilities or other cause or circumstance, similar or otherwise, beyond its control. "
- b) "The seller may decline to deliver hereunder except for cash if at any time the company shall not be satisfied as to the customer's credit or responsibility."
- c) All prices are subject to change without notice.

WARRANTY

"The seller guarantees the said goods against original defects in material or workmanship for (one year) from the date of shipment provided as follows:

- a) the goods are used, operated and maintained in a competent and normal manner by the buyer and in conformity with the seller's instructions;
- b) the seller's liability under this warranty shall be limited to the replacement or repairs of any defective goods, free of charge to the buyer or, at the seller's option a refund of the purchase price less an adjusted charge for the service rendered by the defective goods;
- c) any expressed or implied warranty that the goods are adequate for any particular purpose is hereby negated;
- d) with respect to the goods not of the seller's own manufacture, this warranty shall apply only to the extent that the seller is able to enforce a claim for liability against the manufacturer thereof;
- e) the buyer shall give written notice to the seller forthwith after the discovery of any defect and thereafter shall make further use of the goods at his own risk;
- f) the seller shall not be liable for consequential damages arising out of the installation or use of the said goods;
- g) this warranty is given in lieu of all other warranties, implied, statutory, or otherwise."

CLAIMS

Our liability ceases when the goods are delivered to the Transportation Company and we hold receipt for them. Make your claim on the Transportation Companies for concealed as well as apparent damage, and advise us.

The information presented in this brochure is to be used as a general guide. This literature and other literature from Buchanan Rubber is to provide product options for further investigation by experienced, technically versed users. Due to the varietal nature of operating conditions and applications, the user is solely responsible for making the final selection of the product with full understanding that the performance and safety criteria of the application are met. The product specifications presented here are subject to change without notice.

Table of Contents

Categorized Listing

SHEET RUBBER	1
SHEET RUBBER	1
BUTYL	1
BUTYL	1
CHUTE AND LAUNDER - 1 OUTER FABRIC PLY	1
CHUTE AND LAUNDER - 1 OUTER PLY FABRIC	1
CI PACKING	1
PREMIUM CLOTH INSERTED	1
CLOTH IMPRESSION RED SHEET	2
PREMIUM CLOTH IMPRESSION RED SHEET	2
DIAPHRAGM SHEET NEOPRENE/NYLON	2
REGULAR NEOPRENE DIAPHRAGM SHEET	2
EPDM	3
REGULAR EPDM	3
HYPALON	3
HYPALON	3
MATTING	3
MATTING	3
NEOPRENE	4
REGULAR NEOPRENE	4
NITRILE	5
REGULAR NITRILE	5
PURE GUM	5
REGULAR PURE GUM	5
RED SHEET	6
REGULAR RED SHEET	6
SBR	7
SBR	7
SBR	8
SBR	8
SBR SKIRTBOARD	8
SBR SKIRTBOARD	8
SILICONE	9
REGULAR SILICONE	9
SILICONE SPONGE	9
REGULAR SILICONE SPONGE	9
FKM	9
FKM	9
WHITE NITRILE	10
WHITE NITRILE	10
TECHNICAL INFORMATION	10

SHEET RUBBER

BUTYL

BUTYL



GENERAL CHARACTERISTICS: Excellent heat, ozone, oxidation, UV light, cosmic and ionising radiation resistance. Poor abrasion and fuel resistance

DUROMETER SHORE A: 60

COLOUR: BLACK

ELONGATION %: 350

TENSILE PSI: 1250

TEMPERATURE: 0C to +100C(32F to +230F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
BU60P-006-48	BLACK	100'	1/16	48	0.45
BU60P-013-48	BLACK	50'	1/8	48	0.90
BU60P-025-48	BLACK	50'	1/4	48	1.80

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

CHUTE AND LAUNDRER - 1 OUTER FABRIC PLY

CHUTE AND LAUNDRER - 1 OUTER PLY FABRIC



DUROMETER SHORE A: 55

COLOUR: BLACK

ELONGATION %: 250

TENSILE PSI: 500

TEMPERATURE: -20C TO +75C(-4F TO +170F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
CH-038-48	BLACK	50'	3/8	48	3.00
CH-075-48	BLACK	50'	3/4	48	6.00
CH-100-48	BLACK	50'	1	48	8.00

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

CI PACKING

PREMIUM CLOTH INSERTED



GENERAL CHARACTERISTICS: Low grade packing material.

DUROMETER SHORE A: 60

COLOUR: BLACK

ELONGATION %: 250

TENSILE PSI: 500

TEMPERATURE: -25C TO +85C(-13 TO +185F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"
CI70P-006-48-1	BLACK	100'	1/16	48
CI70P-010-48-1	BLACK	50'	3/32	48
CI70P-013-36-1	BLACK	50'	1/8	36
CI70P-013-36-2	BLACK	50'	1/8	36
CI70P-013-48-1	BLACK	50'	1/8	48
CI70P-013-48-2	BLACK	50'	1/8	48
CI70P-019-36-2	BLACK	50'	3/16	36
CI70P-019-48-2	BLACK	50'	3/16	48
CI70P-025-36-2	BLACK	50'	1/4	36
CI70P-025-48-2	BLACK	50'	1/4	48

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

SHEET RUBBER

CLOTH IMPRESSION RED SHEET

PREMIUM CLOTH IMPRESSION RED SHEET



GENERAL CHARACTERISTICS: Low grade packing material with cloth impression one side.

DUROMETER SHORE A: 65

COLOUR: RED

ELONGATION %: 250

TENSILE PSI: 400

TEMPERATURE: -20C TO +75C (-4F TO +170F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
REDCP80-006-48	RED	100'	1/16	48	0.60
REDCP80-010-48	RED	50'	3/32	48	0.90
REDCP80-013-36	RED	50'	1/8	36	1.20
REDCP80-013-48	RED	50'	1/8	48	1.20
REDCP80-019-36	RED	50'	3/16	36	1.80
REDCP80-019-48	RED	50'	3/16	48	1.80
REDCP80-025-36	RED	50'	1/4	36	2.40
REDCP80-025-48	RED	50'	1/4	48	2.40

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

DIAPHRAGM SHEET NEOPRENE/NYLON

REGULAR NEOPRENE DIAPHRAGM SHEET



GENERAL CHARACTERISTICS: Good resistance to heat, oils, some chemicals and solvents with better tear resistance than all rubber neoprene

DUROMETER SHORE A: 60

COLOUR: BLACK

ELONGATION %: 250

TENSILE PSI: 500

TEMPERATURE: -25C TO +85C (-13F TO +185F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
DIA-006-36-1	BLACK	100'	1/16	36	0.46
DIA-006-48-1	BLACK	50'	1/16	48	0.46
DIA-010-36-1	BLACK	50'	3/32	36	0.70
DIA-010-48-1	BLACK	50'	3/32	48	0.70
DIA-013-36-1	BLACK	50'	1/8	36	0.94
DIA-013-36-2	BLACK	50'	1/8	36	0.96
DIA-013-48-1	BLACK	50'	1/8	48	0.94
DIA-013-48-2	BLACK	50'	1/8	48	0.96
DIA-019-36-2	BLACK	50'	3/16	36	1.40
DIA-019-48-2	BLACK	50'	3/16	48	1.40
DIA-025-48-2	BLACK	50'	1/4	48	1.88

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

Product Information: Suffix on part number indicates the number of plies. -1 = 1ply, -2 = 2ply

SHEET RUBBER

EPDM

REGULAR EPDM



GENERAL CHARACTERISTICS: Excellent ozone and weather resistance. Very Good resistance to heat and has a low gas permeation rate
DUROMETER SHORE A: 60
COLOUR: BLACK
ELONGATION %: 250
TENSILE PSI: 500
TEMPERATURE: -34C to +110C (-30F to +230F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
EP60-006-36	BLACK	100'	1/16	36	0.48
EP60-006-48	BLACK	100'	1/16	48	0.48
EP60-013-36	BLACK	50'	1/8	36	0.96
EP60-013-48	BLACK	50'	1/8	48	0.96
EP60-019-36	BLACK	50'	3/16	36	1.44
EP60-019-48	BLACK	50'	3/16	48	1.44
EP60-025-36	BLACK	50'	1/4	36	1.92
EP60-025-48	BLACK	50'	1/4	48	1.92
EP60-038-36	BLACK	50'	3/8	48	2.88
EP60-038-48	BLACK	50'	3/8	48	2.88
EP60-050-36	BLACK	50'	1/2	48	3.84
EP60-050-48	BLACK	50'	1/2	48	3.84

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

HYPALON

HYPALON



GENERAL CHARACTERISTICS: Good flame and acid resistance. Low resistance to oil and solvents.
DUROMETER SHORE A: 60
COLOUR: BLACK
ELONGATION %: 300
TENSILE PSI: 1200
TEMPERATURE: -29C to +121C (-20F to +250F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
HY60P-006-48	BLACK	100'	1/16	48	0.48
HY60P-013-48	BLACK	50'	1/8	48	0.96
HY60P-019-48	BLACK	50'	3/16	48	1.44
HY60P-025-48	BLACK	50'	1/4	48	1.92

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

MATTING

MATTING



COLOUR: BLACK

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
MATIN-3B	BLACK	3'	5/8	36	17.00
MATIN-3R	BLACK	3'	5/8	36	17.00
MATN-013-36	BLACK	75'	1/8	36	0.83
MATW-013-36	BLACK	75'	1/8	36	0.83
MATW-013-48	BLACK	75'	1/8	48	0.83

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

SHEET RUBBER
NEOPRENE
REGULAR NEOPRENE

GENERAL CHARACTERISTICS: Good resistance to heat, oils, some chemicals and solvents

DUROMETER SHORE A: 50/60/70/80

COLOUR: BLACK

ELONGATION %: 250

TENSILE PSI: 500

TEMPERATURE: -25C to +85C (-13F to +185F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
NEO50-006-36	BLACK	50'	1/16	36	0.48
NEO50-006-48	BLACK	50'	1/16	48	0.48
NEO50-010-36	BLACK	50'	3/32	36	0.73
NEO50-010-48	BLACK	50'	3/32	48	0.73
NEO50-013-36	BLACK	50'	1/8	36	0.98
NEO50-013-48	BLACK	50'	1/8	48	0.98
NEO50-019-36	BLACK	50'	3/16	36	1.47
NEO50-019-48	BLACK	50'	3/16	48	1.47
NEO50-025-36	BLACK	50'	1/4	36	1.93
NEO50-025-48	BLACK	50'	1/4	48	1.93
NEO50-038-36	BLACK	50'	3/8	36	2.94
NEO50-038-48	BLACK	50'	3/8	48	2.94
NEO50-050-36	BLACK	50'	1/2	36	3.84
NEO50-050-48	BLACK	50'	1/2	48	3.84
NEO50-075-48	BLACK	50'	3/4	48	5.79
NEO60-003-36	BLACK	100'	1/32	36	0.22
NEO60-003-48	BLACK	100'	1/32	48	0.22
NEO60-006-36	BLACK	50'	1/16	36	0.48
NEO60-006-48	BLACK	50'	1/16	48	0.48
NEO60-010-36	BLACK	50'	3/32	36	0.73
NEO60-010-48	BLACK	50'	3/32	48	0.73
NEO60-013-36	BLACK	50'	1/8	36	0.98
NEO60-013-48	BLACK	50'	1/8	48	0.98
NEO60-019-36	BLACK	50'	3/16	36	1.47
NEO60-019-48	BLACK	50'	3/16	48	1.47
NEO60-025-36	BLACK	50'	1/4	36	1.93
NEO60-025-48	BLACK	50'	1/4	48	1.93
NEO60-038-36	BLACK	50'	3/8	36	2.94
NEO60-038-48	BLACK	50'	3/8	48	2.94
NEO60-050-36	BLACK	50'	1/2	48	3.80
NEO60-050-48	BLACK	50'	1/2	48	3.84
NEO60-075-36	BLACK	50'	3/4	36	5.79
NEO60-075-48	BLACK	50'	3/4	48	5.79
NEO60-100-36	BLACK	50	1	36	7.68
NEO60-100-48	BLACK	50'	1	48	7.68
NEO60-150-36	BLACK	9'	1-1/2	36	10.55
NEO60-150-48	BLACK	9'	1-1/2	48	11.52
NEO60-200-48	BLACK	9'	2	48	15.36
NEO70-006-48	BLACK	100'	1/16	48	0.48
NEO70-013-36	BLACK	50'	1/16	48	0.98
NEO70-013-48	BLACK	50'	1/8	48	0.98
NEO70-019-36	BLACK	50'	3/16	48	1.45
NEO70-019-48	BLACK	50'	3/16	48	1.45
NEO70-025-36	BLACK	50'	1/4	48	1.93
NEO70-025-48	BLACK	50'	1/4	48	1.93
NEO70-038-36	BLACK	50'	3/8	48	2.64
NEO70-038-48	BLACK	50'	3/8	48	2.64
NEO70-050-48	BLACK	50'	1/2	48	3.84
NEO80-006-36	BLACK	50'	1/16	36	0.48
NEO80-010-36	BLACK	50'	3/32	36	0.73
NEO80-013-36	BLACK	50'	1/8	36	0.98
NEO80-019-36	BLACK	50'	3/16	36	1.45
NEO80-025-36	BLACK	50'	1/4	36	1.93

SHEET RUBBER

NEOPRENE

REGULAR NEOPRENE

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

NITRILE

REGULAR NITRILE



GENERAL CHARACTERISTICS:Very good oil resisitance
DUROMETER SHORE A:60/70
COLOUR:BLACK
ELONGATION %:250
TENSILE PSI:500
TEMPERATURE:-20C to +75C(-4F to +170F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
NIT60-006-36	BLACK	100'	1/16	48	0.49
NIT60-006-48	BLACK	50'	1/16	48	0.49
NIT60-013-36	BLACK	50'	1/8	36	0.98
NIT60-013-48	BLACK	50'	1/8	48	0.98
NIT60-019-36	BLACK	50'	3/16	36	1.47
NIT60-019-48	BLACK	50'	3/16	48	1.47
NIT60-025-36	BLACK	50'	1/4	48	1.96
NIT60-025-48	BLACK	50'	1/4	48	1.96
NIT60-038-36	BLACK	50'	3/8	36	2.94
NIT60-038-48	BLACK	50'	3/8	48	2.94
NIT60-050-36	BLACK	50'	1/2	48	3.92
NIT60-050-48	BLACK	50'	1/2	48	3.92
NIT70-013-48	BLACK	50'	1/8	48	0.98

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

PURE GUM

REGULAR PURE GUM



GENERAL CHARACTERISTICS:Excellent cut and abrasion resistance. Very resilient
DUROMETER SHORE A:40/45
COLOUR:TAN/GREEN
ELONGATION %:600
TENSILE PSI:2500
TEMPERATURE:-34C to +65C(-30F to +150F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
PG40-006-48	TAN	100'	1/16	48	0.33
PG40-013-48	TAN	50'	1/8	48	0.66
PG40-019-48	TAN	50'	3/16	48	0.99
PG40-025-48	TAN	50'	1/4	48	1.32
PG40-038-48	TAN	50'	3/8	48	1.98
PG40-050-48	TAN	50'	1/2	48	2.64
PG40-075-48	TAN	50'	3/4	48	3.96
PG40-100-48	TAN	50'	1	48	5.28
PG40G-025-48	GREEN	50'	1/4	48	1.32
PG40G-038-48	GREEN	50'	3/8	48	1.98
PG40G-050-48	GREEN	50'	1/2	48	2.64
PG40G-075-48	GREEN	50'	3/4	48	3.96

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

SHEET RUBBER**RED SHEET**

REGULAR RED SHEET

GENERAL CHARACTERISTICS:Low grade packing material
DUROMETER SHORE A:65
COLOUR:BLACK
ELONGATION %:250
TENSILE PSI:400
TEMPERATURE:-20C TO +75C(-4F TO =170F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
RED80-006-36	RED	100'	1/16	36	0.60
RED80-006-48	RED	100'	1/16	48	0.60
RED80-010-48	RED	50'	3/32	48	0.90
RED80-013-36	RED	50'	1/8	36	1.20
RED80-013-48	RED	50'	1/8	48	1.20
RED80-019-36	RED	50'	3/16	36	1.80
RED80-019-48	RED	50'	3/16	48	1.80
RED80-025-36	RED	50'	1/4	36	2.40
RED80-025-48	RED	50'	1/4	48	2.40

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

SBR
SBR


GENERAL CHARACTERISTICS: General purpose sheet.
DUROMETER SHORE A: 60/70/80
COLOUR: BLACK
ELONGATION %: 250
TENSILE PSI: 400
TEMPERATURE: -20C to +75C (-4F to +170F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
SB50-006-36	BLACK	100'	1/16	36	0.50
SB50-006-48	BLACK	100'	1/16	48	0.50
SB50-013-36	BLACK	50'	1/8	36	1.00
SB50-013-48	BLACK	50'	1/8	48	1.00
SB50-019-48	BLACK	50'	3/16	48	1.50
SB50-025-36	BLACK	50'	1/4	36	2.00
SB50-025-48	BLACK	50'	1/4	48	2.00
SB50-038-36	BLACK	50'	3/8	36	3.00
SB50-038-48	BLACK	50'	3/8	48	3.00
SB50-050-36	BLACK	50'	1/2	36	4.00
SB50-050-48	BLACK	50'	1/2	48	4.00
SB50-075-36	BLACK	50'	3/4	36	6.00
SB50-075-48	BLACK	50'	3/4	48	6.00
SB50-100-48	BLACK	50'	1	48	8.00
SB60-003-36	BLACK	100'	1/32	36	0.25
SB60-003-48	BLACK	100'	1/32	48	0.25
SB60-006-36	BLACK	50'	1/16	36	0.50
SB60-006-48	BLACK	100'	1/16	48	0.50
SB60-010-36	BLACK	50'	3/32	36	0.75
SB60-010-48	BLACK	50'	3/32	48	0.75
SB60-013-36	BLACK	50'	1/8	36	1.00
SB60-013-48	BLACK	50'	1/8	48	1.00
SB60-019-36	BLACK	50'	3/16	36	1.50
SB60-019-48	BLACK	50'	3/16	48	1.50
SB60-025-36	BLACK	50'	1/4	36	2.00
SB60-025-48	BLACK	50'	1/4	48	2.00
SB60-038-36	BLACK	50'	3/8	36	3.00
SB60-038-48	BLACK	50'	3/8	48	3.00
SB60-050-36	BLACK	50'	1/2	36	4.00
SB60-050-48	BLACK	50'	1/2	48	4.00
SB60-063-48	BLACK	50'	5/8	48	5.00
SB60-075-36	BLACK	50'	3/4	36	6.00
SB60-075-48	BLACK	50'	3/4	48	6.00
SB60-100-36	BLACK	50'	1	36	8.00
SB60-100-48	BLACK	50'	1	48	8.00
SB60-125-48	BLACK	50'	1-1/4	48	7.20
SB60-150-36	BLACK	9'	1-1/2	48	12.00
SB60-150-48	BLACK	9'	1-1/2	48	12.00
SB60-200-36	BLACK	9'	2	36	16.00
SB60-200-48	BLACK	9'	2	48	16.00
SB70-006-48	BLACK	100'	1/16	48	0.50
SB70-013-36	BLACK	50'	1/8	36	1.00
SB70-013-48	BLACK	50'	1/8	48	1.00
SB70-019-48	BLACK	50'	3/16	48	1.50
SB70-025-48	BLACK	50'	1/4	48	2.00
SB70-038-48	BLACK	50'	3/8	48	3.00
SB70-050-48	BLACK	50'	1/2	48	4.00
SB80-050-36	BLACK	50'	1/2	48	4.20
SB80-050-4	BLACK	50'	4	4	1.40
SB80-050-48	BLACK	50'	1/2	48	4.20
SB80-075-48	BLACK	50'	3/4	48	6.30
SB80-100-36	BLACK	50'	1	36	8.40
SB80-100-48	BLACK	50'	1	48	8.40
SB80-100-6	BLACK	50'	1	6	4.20

SHEET RUBBER

SBR

SBR

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
SB80-150-36	BLACK	9'	1-1/2	36	12.60
SB80-150-48	BLACK	9'	1-1/2	48	12.60
SB80-200-48	BLACK	9'	2	48	16.80

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

SBR SKIRTBOARD

SBR SKIRTBOARD



GENERAL CHARACTERISTICS: Skirtboard
DUROMETER SHORE A:55
COLOUR:BLACK
ELONGATION %:250
TENSILE PSI:400
TEMPERATURE:-20C to +75C(-4F to +170F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
SK-025-12	BLACK	50'	1/4	12	2.00
SK-025-4	BLACK	50'	1/4	4	0.67
SK-025-5	BLACK	50'	1/4	5	0.83
SK-025-6	BLACK	50'	1/4	6	1.00
SK-025-8	BLACK	50'	1/4	8	1.33
SK-038-12	BLACK	50'	3/8	12	3.00
SK-038-4	BLACK	50'	3/8	4	1.00
SK-038-6	BLACK	50'	3/8	6	1.50
SK-038-8	BLACK	50'	3/8	8	1.60
SK-050-10	BLACK	50'	1/2	10	3.50
SK-050-12	BLACK	50'	1/2	12	4.00
SK-050-4	BLACK	50'	1/2	4	1.33
SK-050-5	BLACK	50'	1/2	5	1.66
SK-050-6	BLACK	50'	1/2	6	2.00
SK-050-7	BLACK	50'	1/2	7	2.50
SK-050-8	BLACK	50'	1/2	8	3.00
SK-075-12	BLACK	50'	3/4	12	6.00
SK-075-4	BLACK	50'	3/4	4	2.00
SK-075-6	BLACK	50'	3/4	6	3.00
SK-075-8	BLACK	50'	3/4	8	3.50
SK-100-4	BLACK	50'	1	4	3.50
SK-100-6	BLACK	50'	1	6	4.00
SK-100-8	BLACK	50'	1	8	5.00

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

SBR

SHEET RUBBER

SILICONE

REGULAR SILICONE



GENERAL CHARACTERISTICS:Excellent heat, ozone, oxidation, UV light, cosmic and ionising radiation resistance. Poor abrasion and fuel resistance

DUROMETER SHORE A:60

COLOUR:RED

ELONGATION %:300

TENSILE PSI:1000

TEMPERATURE:-45C to +230C(-49F to +446F - up to 486F Intermittently)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
SIL60-006-48	RED	50'	1/16	48	0.51
SIL60-013-36	RED	50'	1/8	36	1.02
SIL60-013-48	RED	50'	1/8	48	1.02
SIL60-019-36	RED	50'	3/16	48	1.53
SIL60-019-48	RED	50'	3/16	48	1.53
SIL60-025-36	RED	50'	1/4	48	2.04
SIL60-025-48	RED	50'	1/4	48	2.04

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

SILICONE SPONGE

REGULAR SILICONE SPONGE



GENERAL CHARACTERISTICS:Excellent heat, ozone, oxidation, UV light, cosmic and ionising radiation resistance. Poor abrasion and fuel resistance

DUROMETER SHORE A:65

COLOUR:RED

ELONGATION %:120

TENSILE PSI:108

TEMPERATURE:-60C to +230C(-76F to +446F - up to 486F Intermittently)

Item No	Colour	Roll Length(FT)	Thickness"	Width"
SILSP-013-36	RED	50'	1/8	36
SILSP-025-36	RED	50'	1/4	36
SILSP-038-36	RED	50'	3/8	36
SILSP-050-36	RED	50'	1/2	36

Cut Charge: Plus 15% for 1/8" and 1/4" in 10' or 25' multiples only or 3/8" and 1/2" in 10' or 20' multiples.

FKM

FKM



GENERAL CHARACTERISTICS:Excellent fuel resistance at elevated temperatures

DUROMETER SHORE A:75

COLOUR:BLACK

ELONGATION %:250

TENSILE PSI:1150

TEMPERATURE:-20C to +240C(-4F to +464F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
VI75-003-48	BLACK	100'	1/32	48	0.34
VI75-006-48	BLACK	100'	1/16	48	0.68
VI75-010-48	BLACK	100'	3/32	48	1.02
VI75-013-48	BLACK	50'	1/8	48	1.36
VI75-019-48	BLACK	50'	3/16	48	2.04
VI75-025-48	BLACK	50'	1/4	48	2.72
VI75-038-48	BLACK	50'	3/8	48	4.08

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

SHEET RUBBER**WHITE NITRILE****WHITE NITRILE****GENERAL CHARACTERISTICS:** Good oil resistance. Food quality FDA Compliant Material**DUROMETER SHORE A:** 60**COLOUR:** WHITE**ELONGATION %:** 210**TENSILE PSI:** 600**TEMPERATURE:** -30C to +100C (-22F to +212F)

Item No	Colour	Roll Length(FT)	Thickness"	Width"	Weight(lbs)
WH60-006-48	WHITE	100'	1/16	48	0.49
WH60-013-36	WHITE	100'	1/8	36	0.97
WH60-013-48	WHITE	50'	1/8	48	0.97
WH60-019-48	WHITE	50'	3/16	48	1.46
WH60-025-48	WHITE	50'	1/4	48	1.95
WH60-038-48	WHITE	50'	3/8	48	2.91
WH60-050-48	WHITE	50'	1/2	48	3.90

Cut Charge: Plus 15%. Cut strips will be price on a per item basis. Please call for pricing.

Table of Contents

Alphabetized Listing

B		
	BUTYL	1
C		
	CHUTE AND LAUNDER - 1 OUTER FABRIC PLY	1
	CHUTE AND LAUNDER - 1 OUTER PLY FABRIC	1
	CI PACKING	1
	CLOTH IMPRESSION RED SHEET	2
D		
	DIAPHRAGM SHEET NEOPRENE/NYLON	2
E		
	EPDM	3
H		
	HYPALON	3
M		
	MATTING	3
N		
	NEOPRENE	4-5
	NITRILE	5
P		
	PREMIUM CLOTH IMPRESSION RED SHEET	2
	PREMIUM CLOTH INSERTED	1
	PURE GUM	5
R		
	RED SHEET	6
	REGULAR EPDM	3
	REGULAR NEOPRENE	4-5
	REGULAR NEOPRENE DIAPHRAGM SHEET	2
	REGULAR NITRILE	5
	REGULAR PURE GUM	5
	REGULAR RED SHEET	6
	REGULAR SILICONE	9
	REGULAR SILICONE SPONGE	9
S		
	SBR	7-8
	SBR SKIRTBOARD	8
	SHEET RUBBER	1-10
	SILICONE	9
	SILICONE SPONGE	9
T		
	TECHNICAL INFORMATION	10
V		
	FKM	9
W		
	WHITE NITRILE	10



BUCHANAN RUBBER LTD.

Buchanan Rubber has been in business for over 25 years. At the time of our inception, most Industrial Hose and Coupling distributors relied on large corporations with high prices, small inventories and long lead times. Our approach to the market was to give these distributors an alternative source of supply. Buchanan Rubber's approach was to concentrate on these three business metrics and offer distributors what they could not consistently receive elsewhere in the market. This approach combined with the practice of staffing our company with Industry professionals has served our customers well over the years. Today, we continue to successfully optimize this model by providing Quality Products, Competitive Prices and Outstanding Service.

We look forward to being of service to your company.

T. 1.888.775.HOSE (4673)
F. 1.888.990.HOSE (4673)
buchananrubber.com

CANADIAN OPERATIONS

TORONTO

50 Fasken Drive, Units 11 - 21
Rexdale, Ontario M9W 1K5
email: sales@buchananrubber.com

EDMONTON

9547 - 12 Ave. SW
Edmonton, Alberta T6X 0C3
email: westernsales@buchananrubber.com


MONTREAL

9555 Henri Bourassa Ouest
Ville St Laurent, Quebec H4S 1S7
email: sales@amiflex.com

USA OPERATIONS

HOUSTON

Hose and Accessory Sales, Inc.
5731 Harvey Wilson Drive Houston, Texas 77020
email: sales@buchananrubber.com



The information presented in this brochure is to be used as a general guide. This literature and other literature from Buchanan Rubber is to provide product options for further investigation by experienced, technically versed users. Due to the varietal nature of operating conditions and applications, the user is solely responsible for making the final selection of the product with full understanding that the performance and safety criteria of the application are met. The product specifications presented here are subject to change without notice.