



ARI SUCTION



- Application** : Used in a variety of material handling application where a good resistance to abrasion is required, such as transfer of sands, plastic pellets, gravel, wood chips, slurries and fly ash. Tube and cover is a specially formulated technical alloy that makes this hose antistatic.
- Cover** : Vinyl modified nitrile
- Reinforcement** : Anti shock rigid pvc helix
- Tube** : An alloy of polyurethane and pvc
- Temperature** : -30C to +65C(-22F to +150F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty	Part #
2"	2.50"	26"	5.50"	70	0.50	100'	ARI-200
2-1/2"	3.00"	26"	6.00"	70	0.88	100'	ARI-250
3"	3.58"	26"	7.00"	60	1.10	100'	ARI-300
4"	4.78"	26"	10.00"	60	2.15	100'	ARI-400
5"	5.77"	26"	16.00"	60	2.62	100'	ARI-500
6"	6.82"	26"	20.00"	60	3.08	100'	ARI-600
8"	9.00"	26"	30.00"	45	5.50	60'	ARI-800

Cut Lengths : Plus 10%
Standard Lengths : 100'
Recommended Couplings : Cam and groove