




PETROLEUM DROP HOSE



- Application** : For use as a tank truck gravity drop hose. Also for use with oil, fuel and grease transfer, oil slurry, hydrocarbons and animal fat handling. Features an external helix that protects the hose cover as well as enabling the hose to slide over rough surface.
- Cover** : Orange PVC Helix
- Reinforcement** : High tensile synthetic textile yarn with built in static wire
- Tube** : Specially formulated compound for fuel transfer
- Temperature** : -29C to +65C(-20F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
2	2.67	28	5.00	70	1.120	100	PDROP-200
3	3.69	28	6.00	65	1.370	100	PDROP-300
4	4.82	28	8.00	65	2.160	100	PDROP-400

Cut Lengths : Plus 10%
Standard Lengths : 50'/100'
Recommended Couplings : Cam and groove

BANDING COILS

Application : Threads between the helix of a hose, this coil provides a smoother surface for banding or crimping.

Nom. I.D (in)	Weight (lbs)	Part #
1-1/2	0.007	COIL-150
2	0.120	COIL-200
2-1/2	0.190	COIL-250
3	0.290	COIL-300
4	0.510	COIL-400
5	0.950	COIL-500
6	1.570	COIL-600
8	2.920	COIL-800

Standard Lengths : Cut each piece in half for each end of hose