




SATURN WHITE PVC WATER SUCTION AND DISCHARGE HOSE



- Application** : An economical, flexible hose for construction pumps, septic tank & marine pump-out service. Resistant to some chemicals, mild acids & alkalis. Consult us for recommendations.
- Cover** : Clear abrasion and weather resistant PVC.
- Reinforcement** : White PVC helix.
- Tube** : Smooth clear PVC.
- Temperature** : -20C to +65C(-4F to +150F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4"	1.02"	28"	3.00"	85	0.20	100'	SATW-075
1"	1.25"	28"	3.00"	80	0.25	100'	SATW-100
1-1/4"	1.53"	28"	3.20"	70	0.33	100'	SATW-125
1-1/2"	1.83"	28"	3.50"	65	0.39	100'	SATW-150
2"	2.35"	28"	5.00"	60	0.60	100'	SATW-200
2-1/2"	2.87"	28"	7.00"	60	0.80	100'	SATW-250
3"	3.40"	28"	9.00"	60	1.00	100'	SATW-300
4"	4.50"	28"	13.00"	50	1.60	100'	SATW-400
6"	6.56"	28"	24.00"	40	2.90	100'	SATW-600

Cut Lengths : Plus 10%

Standard Lengths : 100'

Safety Information : Suction and Pressure ratings are based on a temperature of 20C (68F), reduce by 50% at maximum working temperature

Recommended Couplings : Cam and groove or short shank