




# B - FLEX (STATIC) (FOOD GRADE)



- Application** : Conveying of dry powders, grains and plastic pellets where viewing the product, flexibility and static electricity is important.
- Cover** : Corrugated clear PVC.
- Reinforcement** : Clear rigid PVC helix with integral static wire.
- Tube** : Smooth clear PVC
- Temperature** : -23C to +65C(-10F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
1 1/2	1.83	29	2.50	35	0.280	100	BFLST-150
2	2.35	29	3.00	35	0.440	100	BFLST-200
2 1/2	2.90	29	5.00	30	0.600	100	BFLST-250
3	3.50	29	6.00	25	0.850	100	BFLST-300
39mm	1.88	29	3.00	45	0.290	100	BFLST-39-MM

**Cut Lengths** : Plus 10%

**Standard Lengths** : 100'

**Product Information** : Compliant with the applicable requirements and standards of FDA USDA and 3-A.

**Safety Information** : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature

**Recommended Couplings** : Cam and groove