



**BULKMASTER SOFTWALL**



- Application** : Dry bulk discharge including limestone, ground silica, chalk, dry cement, fertilizer etc. May also be used for wet abrasive applications.
- Cover** : Black abrasion and weather resistant synthetic rubber. Green stripe on 1/4" thick tube.
- Reinforcement** : Multiple layers of high tensile synthetic cords.
- Tube** : Black abrasion resistant natural rubber in 1/8", 3/16" and 1/4"
- Temperature** : -30C to +80C(-25F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
3"	3.62"	75	1.78	100'	BSB-300-187
4"	4.49"	75	1.50	100'	BSB-400-125
4"	4.64"	75	2.15	100'	BSB-400-187
4"	4.72"	75	2.60	100'	BSB-400-250
4"	5.00"	75	3.40	100'	BSB-400-375
4-1/2"	5.00"	75	1.80	100'	BSB-450-125
5"	5.51"	75	2.10	100'	BSB-500-125
5"	5.63"	75	2.52	100'	BSB-500-187
5"	5.79"	75	3.50	100'	BSB-500-250
5"	5.93"	75	3.00	100'	BSB-500-313
6"	6.65"	75	3.30	100'	BSB-600-187
6"	6.81"	75	3.84	100'	BSB-600-250

**Cut Lengths** : Plus 10%  
**Standard Lengths** : 100'