



CONTRACTORS AIR



- Application** : For mining, construction, and industrial use
- Cover** : Yellow cut and abrasion resistant rubber
- Reinforcement** : Multiple layers of synthetic yarn
- Tube** : Synthetic oil mist resistant
- Temperature** : -35C to +80C(-30F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1/2"	0.91"	300	0.32	50'	CAY-050-50
1/2"	0.91"	300	0.32	100'	CAY-050-100
3/4"	1.18"	300	0.48	50'	CAY-075-50
3/4"	1.18"	300	0.48	100'	CAY-075-100
1"	1.50"	300	0.70	50'	CAY-100-50
1"	1.50"	300	0.70	100'	CAY-100-100
1-1/4"	1.69"	300	0.73	50'	CAY-125-50
1-1/4"	1.69"	300	0.73	100'	CAY-125-100
1-1/2"	1.97"	300	0.93	50'	CAY-150-50
1-1/2"	1.97"	300	0.93	100'	CAY-150-100
2"	2.60"	300	1.56	50'	CAY-200-50
2"	2.60"	300	1.56	100'	CAY-200-100
2-1/2"	3.03"	250	1.67	100'	CAY-250
3"	3.66"	250	2.00	100'	CAY-300
4"	4.68"	250	2.71	100'	CAY-400

Cut Lengths : Plus 10%

Standard Lengths : 50'/100'

Recommended Couplings : High Pressure all sizes, mine stem and nut 1/2" - 2", Universal quick acting 1/2" - 1"