




## EPR ACID DISCHARGE




- Application** : Resistant to a wide range of chemicals, acids, and alcohols. Contact us for recommendations.
- Cover** : Grey chemical and abrasion resistant EPDM rubber with purple identification stripe.
- Reinforcement** : Multiple layers of synthetic yarn.
- Tube** : White chemical, acid, and heat resistant EPDM rubber.
- Temperature** : -40C to +120C(-40F to +248F)

| Nom. I.D | Nom. O.D | PSI | Weight (lbs) | Std Pack Qty | Part #  |
|----------|----------|-----|--------------|--------------|---------|
| 1"       | 1.50"    | 150 | 0.54         | 100'         | EAD-100 |
| 1-1/2"   | 2.05"    | 150 | 0.83         | 100'         | EAD-150 |
| 2"       | 2.68"    | 150 | 1.30         | 100'         | EAD-200 |
| 2-1/2"   | 3.20"    | 150 | 1.62         | 100'         | EAD-250 |
| 3"       | 3.78"    | 150 | 2.10         | 100'         | EAD-300 |

**Cut Lengths** : Plus 10%  
**Standard Lengths** : 100'  
**Recommended Couplings** : Cam and groove

## EPR ACID SUCTION



- Application** : Resistant to a wide range of chemicals, acids, and alcohols. Contact us for recommendations.
- Cover** : Grey chemical and abrasion resistant EPDM rubber with purple identification stripe.
- Reinforcement** : High tensile steel wire helix embedded between layers of synthetic yarns.
- Tube** : White chemical, acid, and heat resistant EPDM rubber.
- Temperature** : -40C to +120C(-40F to +248F)

| Nom. I.D | Nom. O.D | Vacuum (Hg) | Bend Radius | PSI | Weight (lbs) | Std Pack Qty | Part #  |
|----------|----------|-------------|-------------|-----|--------------|--------------|---------|
| 1"       | 1.50"    | 28"         | 7.00"       | 150 | 0.56         | 100'         | EAS-100 |
| 1-1/2"   | 2.16"    | 28"         | 11.00"      | 150 | 1.04         | 100'         | EAS-150 |
| 2"       | 2.68"    | 28"         | 14.00"      | 150 | 1.54         | 100'         | EAS-200 |
| 3"       | 3.74"    | 28"         | 20.00"      | 150 | 2.68         | 100'         | EAS-300 |
| 4"       | 4.76"    | 28"         | 28.00"      | 150 | 4.09         | 100'         | EAS-400 |

**Cut Lengths** : Plus 10%  
**Standard Lengths** : 100'  
**Recommended Couplings** : Cam and groove