



FOODFLEX PVC S&D (FOOD QUALITY)



- Application** : For liquid or dry bulk foodstuffs, pharmaceuticals, cosmetics, milk, fruit and vegetable juices, soft drinks, alcoholic beverages, flour, sugar, poultry or meat packing etc. Clear wall allows visual inspection of the product.
- Cover** : Clear PVC non-marking.
- Reinforcement** : Clear rigid PVC helix.
- Tube** : Smooth clear PVC.
- Temperature** : -23C to +65C(-10F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4	0.95	29	2.00	85	0.160	100	FPVC-075
1	1.24	29	3.00	80	0.260	100	FPVC-100
1 1/4	1.54	29	4.00	80	0.340	100	FPVC-125
1 1/2	1.81	29	5.00	70	0.440	100	FPVC-150
2	2.39	29	7.00	70	0.750	100	FPVC-200
3	3.43	29	10.00	60	1.210	100	FPVC-300
4	4.54	29	14.00	50	2.020	100	FPVC-400

Cut Lengths : Plus 10%

Standard Lengths : 50'/100'

Product Information : Compliant with the applicable requirements and standards of FDA USDA and 3-A

Safety Information : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature

Recommended Couplings : Cam and groove or Sanitary