



GENERAL PURPOSE



- Application** : General air-line and water service both in plant and outdoors
- Cover** : Red smooth weather and abrasion resistant synthetic rubber
- Reinforcement** : Multiple layers of synthetic yarns
- Tube** : Black oil mist resistant synthetic rubber
- Temperature** : -30C to +70C(-22F to +160F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1/4"	0.55"	250	0.13	300'	GP-025-250
3/8"	0.67"	200	0.19	300'	GP-038-200
3/8"	0.71"	250	0.19	300'	GP-038-250
1/2"	0.83"	200	0.23	300'	GP-050-200
1/2"	0.87"	250	0.27	300'	GP-050-250
3/4"	1.16"	250	0.42	300'	GP-075-250
1"	1.42"	200	0.54	300'	GP-100-200
1-1/4"	1.73"	150	0.64	100'	GP-125-150
1-1/2"	2.05"	150	0.74	100'	GP-150-150
2"	2.60"	150	1.01	100'	GP-200-150

Cut Lengths : Plus 5%

Standard Lengths : 1/4"- 1" 50'/100'/300'. 1-1/4" - 2" 50'/100'.

Recommended Couplings : High Pressure 1" - 1-1/2" for air service if the working pressure exceeds 150 psi. High Pressure, Short shank, universal, or Combination nipples all other sizes.