



GREY PVC VACUUM



- Application** : An economical hose for suction of air, fumes, sawdust, and powders in light duty applications.
- Cover** : Grey corrugated PVC for maximum flexibility.
- Reinforcement** : Rigid PVC helix.
- Tube** : Smooth grey PVC.
- Temperature** : -23C to +65C(-10F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4	1.02	28	1.00	30	0.080	100	GRVAC-075
1	1.20	28	2.00	28	0.130	100	GRVAC-100
1 1/4	1.46	28	2.50	22	0.160	100	GRVAC-125
1 1/2	1.79	28	2.50	22	0.240	100	GRVAC-150
2	2.30	28	3.00	15	0.350	100	GRVAC-200
2 1/2	2.76	28	5.00	15	0.510	100	GRVAC-250
3	3.43	28	6.00	15	0.710	100	GRVAC-300
4	4.55	28	9.00	15	1.150	100	GRVAC-400

Cut Lengths : Plus 10%

Standard Lengths : 100'

Safety Information : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature