




**HEAVY DUTY WATER DISCHARGE/LOW PRESSURE AIR**



- Application** : A heavy duty hose for water discharge, and light duty air service up to 100 psi for sizes up to 2 only.
- Cover** : Green abrasion and weather resistant synthetic rubber.
- Reinforcement** : Multiple layers of synthetic yarn.
- Tube** : Black synthetic rubber compounded for water service.
- Temperature** : -35C to +80C(-30F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1-1/4"	1.65"	150	0.61	100'	HDWG-125
1-1/2"	1.95"	150	0.79	100'	HDWG-150
2"	2.52"	150	1.25	100'	HDWG-200
2-1/2"	2.99"	150	1.44	100'	HDWG-250
3"	3.50"	125	1.78	100'	HDWG-300
4"	4.50"	125	2.51	100'	HDWG-400
5"	5.50"	125	2.40	100'	HDWG-500
6"	6.49"	125	4.29	100'	HDWG-600
8"	8.58"	125	5.06	100'	HDWG-800
10"	10.67"	125	6.27	50'	HDWG-1000
12"	12.67"	100	6.30	50'	HDWG-1200

**Cut Lengths** : Plus 10%  
**Standard Lengths** : 50'/100'  
**Recommended Couplings** : Cam and groove or short shank