

Safety Information : Working Temperature ratings are based on new cam and groove couplings at ambient temperatures. Used or worn couplings or extreme temperature conditions will result in reduced operating pressures. Not for use with compressed gases.

PART C ALUM HD TANK TRUCK WITH RETAINING LIP

Application : These heavy duty sand cast couplings feature a thicker wall design and offer superior ductility over dies cast couplings. The two serration shank work well with Hammerlock or bolt clamps.

Vacuum Rating : FULL

Gasket Material : NBR

Gasket Temp. : -40C to +100C(-40F to +212F)

Casting Temp. : -101C to +121C(-150F to +250F)



Size (in)	Max Operating PSI (70F)	Weight (lbs)	Std Pack Qty	Part #
3	150	2.500	10	CGCR-300-A
4	150	3.400	4	CGCR-400-A

PART C ALUM HD TANK TRUCK WITH MULTI-SERRATION

Application : These heavy duty sand cast couplings feature a slab wall design and offer superior ductility over dies cast couplings. The multi serration shank give gives great retention whether using Hammerlock clamps or Quicklok crimp sleeves.

Vacuum Rating : FULL

Gasket Material : NBR

Gasket Temp. : -40C to +100C(-40F to +212F)

Casting Temp. : -101C to +121C(-150F to +250F)



Size (in)	Max Operating PSI (70F)	Weight (lbs)	Std Pack Qty	Part #
3	150	3.050	10	CGCT-300-A
4	150	3.700	4	CGCT-400-A