



HIGH PRESSURE CONTRACTORS WATER DISCHARGE



- Application** : For use on construction sites and general water service. High pressure allows pumping against greater vertical heads
- Cover** : Black abrasion and weather resistant synthetic rubber, with embossed brand and pressure.
- Reinforcement** : Multiple layers of synthetic yarn.
- Tube** : Black synthetic rubber compounded for water service.
- Temperature** : -35C to +80C(-30F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1-1/4"	1.54"	150	0.37	100'	HPCWB-125
1-1/2"	1.77"	150	0.43	100'	HPCWB-150
2"	2.28"	150	0.48	100'	HPCWB-200
2-1/2"	2.79"	150	0.76	100'	HPCWB-250
3"	3.35"	150	1.08	100'	HPCWB-300
4"	4.37"	150	1.38	100'	HPCWB-400
6"	6.46"	150	2.62	100'	HPCWB-600
8"	8.54"	150	4.20	100'	HPCWB-800
10"	10.55"	150	5.78	50'	HPCWB-1000

Cut Lengths : Plus 10%
Standard Lengths : 50'/100'
Recommended Couplings : Cam and groove or short shank