



HYPALON ACID DISCHARGE



- Application** : Resistant to a wide range of chemicals, acids, and alcohols. Contact us for recommendations.
- Cover** : Yellow chemical and abrasion resistant nitrile rubber with green identification stripe.
- Reinforcement** : Multiple layers of synthetic yarn
- Tube** : Black chemical resistant Hypalon.
- Temperature** : -32C to +82C(-25F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4"	1.25"	150	0.45	100'	HLD-075
1"	1.50"	150	0.58	100'	HLD-100
1-1/2"	2.05"	150	0.90	100'	HLD-150
2"	2.68"	150	1.40	100'	HLD-200
3"	3.74"	150	2.45	100'	HLD-300
4"	4.74"	150	3.20	100'	HLD-400

Cut Lengths : Plus 10%
Standard Lengths : 100'
Recommended Couplings : Cam and groove

HYPALON ACID SUCTION



- Application** : Resistant to a wide range of chemicals, acids, and alcohols. Contact us for recommendations.
- Cover** : Yellow chemical and abrasion resistant nitrile rubber with green identification stripe.
- Reinforcement** : High tensile steel wire helix embedded between layers of synthetic yarns.
- Tube** : Black chemical resistant Hypalon.
- Temperature** : -32C to +82C(-25F to +180F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty	Part #
1"	1.50"	28"	6.00"	150	0.60	100'	HLS-100
1-1/2"	2.06"	28"	10.00"	150	1.10	100'	HLS-150
2"	2.68"	28"	12.00"	150	1.70	100'	HLS-200
3"	3.74"	28"	17.00"	150	3.71	100'	HLS-300

Cut Lengths : Plus 10%
Standard Lengths : 100'
Recommended Couplings : Cam and groove