



# INDUSTRIAL VACUUM



- Application** : For handling abrasive dust from wood, metal, rock, marble and concrete grinding machines under vacuum.
- Cover** : Black abrasion resistant rubber, corrugated for flexibility.
- Reinforcement** : A high tensile steel helix embedded between layers of textile cords.
- Tube** : 1/16 black abrasion resistant synthetic rubber standard. 1/8 thick tube stocked in 4", other sizes available on request.
- Temperature** : -30C to +80C(-25F to +180F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty	Part #
1"	1.38"	24"	4.00"	40	0.39	100'	IVB-100
1-1/4"	1.65"	24"	5.00"	40	0.48	100'	IVB-125
1-1/2"	1.97"	24"	6.00"	40	0.60	100'	IVB-150
2"	2.40"	20"	7.00"	40	0.70	100'	IVB-200
2-1/2"	2.95"	18"	10.00"	40	1.03	100'	IVB-250
3"	3.42"	14"	12.00"	40	1.20	100'	IVB-300
3-1/2"	3.90"	12"	14.00"	40	1.29	100'	IVB-350
4"	4.45"	12"	15.00"	40	1.98	100'	IVB-400
4-1/2"	4.96"	10"	18.00"	40	2.05	100'	IVB-450
5"	5.51"	10"	22.00"	40	2.87	100'	IVB-500
6"	6.53"	10"	24.00"	40	3.84	100'	IVB-600

**Cut Lengths** : Plus 10%  
**Standard Lengths** : 100'  
**Recommended Couplings** : Cam and groove