



# INDUSTRIAL VACUUM HEAVY DUTY



- Application** : For handling abrasive dust from wood, metal, rock, marble and concrete grinding machines under vacuum.
- Cover** : Black abrasion resistant rubber, corrugated for flexibility.
- Reinforcement** : A high tensile steel helix embedded between layers of textile cords.
- Tube** : 1/4" or 1/8" red Pure Gum abrasion resistant rubber standard.
- Temperature** : -30C to +80C(-25F to +180F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty	Part #
3"	3.58"	28"	15.00"	90	1.61	100'	IVB-300-125RPG
4"	4.61"	28"	20.00"	90	2.35	100'	IVB-400-125RPG
4"	4.88"	28"	20.00"	90	3.11	100'	IVB-400-250RPG
6"	6.65"	28"	24.00"	60	4.08	100'	IVB-600-125RPG
6"	6.95"	28"	24.00"	60	5.91	100'	IVB-600-250RPG
8"	8.78"	28"	30.00"	50	7.48	100'	IVB-800-125RPG
8"	9.01"	28"	30.00"	50	10.23	100'	IVB-800-250RPG

**Cut Lengths** : Plus 10%

**Standard Lengths** : 100'

**Recommended Couplings** : Cam and groove