



REGULAR NEOPRENE

General : Good resistance to heat, oils, some chemicals and solvents

Characteristics

Durometer Shore A : 50/60/70/80

Colour : BLACK

Elongation % : 250

Tensile PSI : 500

Temperature : -25C to +85C(-13F to +185F)

Thickness	Width	Roll Length	Weight (lbs)	Part #
1/32"	36"	100'	0.22	NEO60-003-36
1/32"	48"	100'	0.22	NEO60-003-48
1/16"	36"	50'	0.48	NEO60-006-36
1/16"	48"	50'	0.48	NEO60-006-48
3/32"	36"	50'	0.73	NEO60-010-36
3/32"	48"	66'	0.73	NEO60-010-48
1/8"	36"	50'	0.98	NEO60-013-36
1/8"	48"	66'	0.98	NEO60-013-48
3/16"	36"	50'	1.47	NEO60-019-36
3/16"	48"	66'	1.47	NEO60-019-48
1/4"	36"	50'	1.93	NEO60-025-36
1/4"	48"	50'	1.93	NEO60-025-48
3/8"	36"	50'	2.94	NEO60-038-36
3/8"	48"	50'	2.94	NEO60-038-48
1/2"	48"	50'	3.84	NEO60-050-48
3/4"	36"	50'	5.79	NEO60-075-36
3/4"	48"	50'	5.79	NEO60-075-48
1"	48"	50'	7.68	NEO60-100-48
1-1/2"	36"	9'	10.55	NEO60-150-36
1-1/2"	48"	9'	11.52	NEO60-150-48
2"	48"	9'	15.36	NEO60-200-48

Cut Charge : Plus 15%, Cut strips will be priced on a per item basis. Please call for pricing.