




NEPTUNE PVC SUCTION (FOOD GRADE)



- Application** : Suction and discharge of liquids and powders where moderate abrasion is a factor.
- Cover** : Corrugated clear PVC.
- Reinforcement** : Clear rigid PVC helix
- Tube** : Smooth clear PVC.
- Temperature** : -23C to +65C(-10F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
1	1.30	28	2.00	55	0.210	100	NEP-100
1-1/2	1.92	28	3.00	50	0.350	100	NEP-150
2	2.40	28	4.00	40	0.560	100	NEP-200
2-1/2	2.99	28	5.00	40	0.770	100	NEP-250
3	3.64	28	6.00	40	1.100	100	NEP-300
4	4.72	24	10.00	35	1.800	100	NEP-400
5	5.74	24	16.00	30	2.340	100	NEP-500
6	6.91	24	18.00	30	3.700	100	NEP-600
8	8.97	20	36.00	20	5.530	60	NEP-800

Cut Lengths : Plus 10%

Standard Lengths : 1" - 6" - 100'

Product Information : Compliant with the applicable requirements and standards of FDA USDA and 3-A.

Safety Information : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature

Recommended Couplings : Cam and groove