



# NEPTUNE STATIC PVC SUCTION (FOOD GRADE)



- Application** : Suction and discharge of liquids and powders where moderate abrasion is a factor.  
Built in static wire assists in dissipating static electricity.
- Cover** : Corrugated clear PVC.
- Reinforcement** : Clear rigid PVC helix with integral static wire.
- Tube** : Smooth clear PVC.
- Temperature** : -23C to +65C(-10F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
1-1/2	1.93	28	3.00	50	0.430	100	NEPST-150
2	2.48	28	4.00	40	0.580	100	NEPST-200
2-1/2	3.07	28	5.00	40	0.890	100	NEPST-250
3	3.64	28	6.00	40	1.250	100	NEPST-300
4	4.72	24	10.00	35	1.930	100	NEPST-400
5	5.74	24	16.00	30	2.530	100	NEPST-500
6	6.81	24	18.00	30	3.700	100	NEPST-600

**Cut Lengths** : Plus 10%

**Standard Lengths** : 1-1/2" - 6" - 100'

**Product Information** : Compliant with the applicable requirements and standards of FDA USDA and 3-A.

**Safety Information** : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature

**Recommended Couplings** : Cam and groove