



# POLYETHYLENE TUBING



**Application** : Instrumentation tubing and transmission lines for air, liquids and gases.  
**Cover** : Low density extruded milky-white polyethylene tubing manufactured from top quality FDA approved virgin resins.  
**Temperature** : -45C to 65C(-50F to +150F)

Nom. I.D	Nom. O.D	Wall Thickness	PSI	Std Pack Qty	Weight (lbs)	Part #
1/8"	1/4"	1/16"	150	2000'	0.01	PET-013-025
0.17"	1/4"	0.040	140	2000'	0.01	PET-017-025
0.17"	1/4"	0.040	140	100'	0.01	PET-017-025-100
3/16"	5/16"	1/16"	150	1500'	0.02	PET-019-031
1/4"	3/8"	1/16"	125	500'	0.03	PET-025-038
1/4"	3/8"	1/16"	125	100'	0.03	PET-025-038-100
3/8"	1/2"	1/16"	100	500'	0.04	PET-038-050
3/8"	1/2"	1/16"	100	100'	0.04	PET-038-050-100
1/2"	5/8"	1/16"	75	500'	0.04	PET-050-063
1/2"	5/8"	1/16"	75	100'	0.05	PET-050-063-100

**Cut Lengths** : Plus 30%  
**Standard Lengths** : 500'