




**PREMIUM GENERAL PURPOSE - NON CONDUCTIVE**



- Application** : A premium quality long length hose for petroleum based fluids, lubricating oils, air, hot water and some chemical solutions
- Cover** : Red, oil, grease, weather and abrasion resistant nitrile
- Reinforcement** : Multiple layers of synthetic yarn
- Tube** : Black oil resistant nitrile rubber
- Temperature** : -32C to +85C (-25F to +185F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1/4"	0.51"	300	0.12	300'	PREM-025-300
3/8"	0.67"	300	0.17	300'	PREM-038-300
1/2"	0.79"	300	0.21	300'	PREM-050-300
3/4"	1.14"	300	0.43	300'	PREM-075-300
1"	1.42"	300	0.60	300'	PREM-100-300
1-1/4"	1.77"	250	0.70	100'	PREM-125-250
1-1/2"	2.05"	250	0.87	100'	PREM-150-250

**Cut Lengths** : Plus 5%

**Standard Lengths** : 1/4"- 1" 50'/300' reels approx, 1-1/4" - 1-1/2" 50'/100'

**Recommended Couplings** : High Pressure 1" - 1-1/2" for air service if the working pressure exceeds 150 psi. High Pressure, Short shank, universal, or Combination nipples all other sizes.