




PU VAC (FOOD GRADE)



- Application** : Ideal for applications where conventional rubber or PVC hose will wear rapidly, i.e. grain transfer, dry foodstuff, abrasive powder recovery, leaf collection. Not recommended for handling liquids
- Cover** : Corrugated clear abrasion and weather resistant Polyurethane.
- Reinforcement** : Grey PVC helix.
- Tube** : Smooth clear abrasion resistant Polyurethane.
- Temperature** : -40C to +65C(-40F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
1 1/2	1.85	29	2.00	50	0.420	100	PU-150
2	2.41	29	3.00	45	0.590	100	PU-200
2 1/2	3.08	29	3.00	40	0.810	100	PU-250
3	3.65	29	4.00	40	1.180	100	PU-300
4	4.76	29	6.00	35	1.950	100	PU-400
5	5.75	28	10.00	35	2.430	100	PU-500
6	6.80	28	12.00	30	3.510	100	PU-600

Cut Lengths : Plus 10%

Standard Lengths : 100'

Product Information : Compliant with the applicable requirements and standards of FDA USDA and 3-A.

Safety Information : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature

Recommended Couplings : Cam and groove