




PU VAC LIGHT (FOOD QUALITY)



- Application** : Handling abrasive fine powders under low pressure or vacuum. Not recommended for handling liquids.
- Cover** : Corrugated clear abrasion and weather resistant Polyurethane.
- Reinforcement** : Rigid grey PVC helix.
- Tube** : Smooth clear abrasion resistant Polyurethane.
- Temperature** : -40C to +65C(-40F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
1 1/2	1.82	14	0.80	20	0.320	100	PUL-150
2	2.39	12	1.40	15	0.320	100	PUL-200
2 1/2	2.87	10	1.50	10	0.410	100	PUL-250
3	3.46	10	2.50	10	0.550	100	PUL-300
4	4.50	8	3.00	9	0.780	100	PUL-400
5	5.52	7	4.00	7	0.890	100	PUL-500
6	6.55	5	5.00	6	1.150	100	PUL-600
8	9.17	3	18.00	3	1.770	100	PUL-800

Cut Lengths : Plus 10%

Standard Lengths : 100'

Product Information : Compliant with the applicable requirements and standards of FDA USDA and 3-A.

Safety Information : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature

Recommended Couplings : Cam and groove