




PU VAC STATIC (FOOD QUALITY)



- Application** : Ideal for applications where conventional rubber or PVC hose will wear rapidly, i.e. grain transfer, dry foodstuff, abrasive powder recovery, leaf collection. Built in static wire assists in dissipating static electricity. Not recommended for handling liquids
- Cover** : Corrugated clear abrasion and weather resistant Polyurethane.
- Reinforcement** : Rigid grey PVC helix with integral static wire.
- Tube** : Smooth clear abrasion resistant Polyurethane.
- Temperature** : -40C to +65C(-40F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
1 1/2	1.85	29	2.00	50	0.420	100	PUST-150
2	2.41	29	3.00	45	0.590	100	PUST-200
2 1/2	2.87	29	3.00	40	0.810	100	PUST-250
3	3.65	29	4.00	40	1.810	100	PUST-300
4	4.76	29	6.00	35	1.950	100	PUST-400
6	6.55	28	12.00	30	3.510	100	PUST-600

Cut Lengths : Plus 10%
Standard Lengths : 100'
Product Information : Compliant with the applicable requirements and standards of FDA USDA and 3-A.
Safety Information : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature
Recommended Couplings : Cam and groove