



**REINFORCED CLEAR PVC**



- Application** : An economical hose for handling air, water, oil, mild chemicals, and alkalis. Clear wall allows visual inspection of product.
- Cover** : Clear smooth PVC
- Reinforcement** : Multiple layers of synthetic yarns
- Temperature** : -5C to +65C(+25F to +150F)

| Nom. I.D | Nom. O.D | PSI | Weight (lbs) | Std Pack Qty | Part #    |
|----------|----------|-----|--------------|--------------|-----------|
| 3/16"    | 0.38"    | 250 | 0.05         | 300'         | RCPVC-019 |
| 1/4"     | 0.46"    | 250 | 0.07         | 300'         | RCPVC-025 |
| 5/16"    | 0.53"    | 250 | 0.08         | 300'         | RCPVC-031 |
| 3/8"     | 0.60"    | 250 | 0.09         | 300'         | RCPVC-038 |
| 1/2"     | 0.75"    | 200 | 0.15         | 300'         | RCPVC-050 |
| 5/8"     | 0.88"    | 200 | 0.17         | 300'         | RCPVC-063 |
| 3/4"     | 1.03"    | 150 | 0.23         | 300'         | RCPVC-075 |
| 1"       | 1.31"    | 125 | 0.32         | 300'         | RCPVC-100 |
| 1-1/4"   | 1.69"    | 100 | 0.58         | 300'         | RCPVC-125 |
| 1-1/2"   | 1.94"    | 100 | 0.69         | 300'         | RCPVC-150 |
| 2"       | 2.50"    | 75  | 1.00         | 300'         | RCPVC-200 |

**Cut Lengths** : Plus 10%

**Standard Lengths** : 3/16"-3/4" 300' coil, 1" 200' coil, 1-1/4"-2" 100' coil

**Recommended Couplings** : Combination nipples, short shank, brass barbed, cam and groove