




## TEXTILE REINFORCED S&D



- Application** : Good for both suction and discharge applications, this heavy duty hose can be used for rental/construction pumping as well as fish suction hose.
- Cover** : Clear abrasion and weather resistant PVC.
- Reinforcement** : Orange PVC helix with high tensile synthetic textile yarn.
- Tube** : Smooth clear PVC.
- Temperature** : -23C to +65C(-10F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
2	2.59	29	4.00	110	0.650	100	RSPVC-200
2 1/2	3.01	29	5.00	100	0.750	100	RSPVC-250
3	3.71	29	6.00	100	1.120	100	RSPVC-300
4	4.78	29	7.00	80	1.740	100	RSPVC-400
5	6.05	28	9.00	75	2.950	100	RSPVC-500
6	7.17	28	10.50	70	3.870	100	RSPVC-600
8	9.33	28	16.00	60	5.520	40	RSPVC-800
10	11.54	28	25.00	40	8.690	20	RSPVC-1000

**Cut Lengths** : Plus 10%

**Standard Lengths** : 100'

**Safety Information** : Suction and Pressure ratings are based on a temperature of 20C (68F), reduce by 50% at maximum working temperature

**Recommended Couplings** : Cam and groove or short shank