



**RUBBER WATER S&D**



- Application** : A heavy duty wire reinforced rubber suction hose for construction, quarries and general use.
- Cover** : Black smooth abrasion and weather resistant synthetic rubber.
- Reinforcement** : High tensile wire helix embedded between layers of textile cords.
- Tube** : Smooth black synthetic rubber.
- Temperature** : -30C to +80C(-22F to +180F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4"	1.14"	29"	2.00"	200	0.50	100'	WSB-075
1"	1.42"	29"	3.00"	150	0.68	100'	WSB-100
1-1/4"	1.65"	29"	4.00"	150	0.77	100'	WSB-125
1-1/2"	1.93"	29"	4.00"	150	1.00	100'	WSB-150
2"	2.48"	29"	5.00"	150	1.45	100'	WSB-200
2-1/2"	2.99"	29"	8.00"	150	1.84	100'	WSB-250
3"	3.50"	29"	10.00"	150	2.23	100'	WSB-300
4"	4.64"	29"	14.00"	125	3.72	100'	WSB-400
5"	5.67"	29"	20.00"	125	3.90	100'	WSB-500
6"	6.66"	29"	30.00"	125	5.10	100'	WSB-600
8"	8.90"	29"	65.00"	50	8.83	60'	WSB-800
10"	10.90"	29"	80.00"	50	12.00	40'	WSB-1000
12"	12.99"	29"	100.00"	50	18.57	20'	WSB-1200

**Cut Lengths** : Plus 10%

**Standard Lengths** : 3/4" to 4" - 50'/100' -- 5" and 6" - 20'/100' -- 8" - 20'/60' -- 10" - 40' -- 12" - 20'

**Recommended Couplings** : Cam and groove or Short Shank