



SAE 100R4 OIL SUCTION HOSE



- Application** : A high quality oil suction hose specifically designed for hydraulic suction service.
- Cover** : Black, abrasion, gasoline and oil resistant synthetic rubber with blue stripe and pressure
- Reinforcement** : High tensile wire helix embedded between layers of textile cords.
- Tube** : Black nitrile rubber for maximum oil resistance.
- Temperature** : -35C to +93C(-30F to +200F)

| Nom. I.D | Nom. O.D | Vacuum (Hg) | PSI | Bend Radius | Weight (lbs) | Std Pack Qty | Part # |
|----------|----------|-------------|-----|-------------|--------------|--------------|----------|
| 3/4" | 1.26" | 29" | 300 | 3.00" | 0.62 | 100' | 100R4-12 |
| 1" | 1.50" | 29" | 250 | 4.00" | 0.74 | 100' | 100R4-16 |
| 1-1/4" | 1.73" | 29" | 200 | 6.00" | 1.01 | 100' | 100R4-20 |
| 1-1/2" | 1.97" | 29" | 150 | 7.00" | 1.01 | 100' | 100R4-24 |
| 2" | 2.56" | 29" | 100 | 8.00" | 1.47 | 100' | 100R4-32 |
| 2-1/2" | 2.99" | 29" | 65 | 10.00" | 1.67 | 100' | 100R4-40 |
| 3" | 3.55" | 29" | 55 | 12.00" | 2.18 | 100' | 100R4-48 |
| 4" | 4.56" | 29" | 35 | 18.00" | 3.10 | 100' | 100R4-64 |

Cut Lengths : Plus 10%
Standard Lengths : 100'
Recommended Couplings : Swaged hydraulic