




SATURN LOW TEMPERATURE PVC WATER S&D



- Application** : An economical, flexible hose for construction pumps, septic tank & marine pump-out service. Resistant to some chemicals, mild acids & alkalis. Consult us for recommendations. Specially formulated compounds allow for increased flexibility at low temperatures.
- Cover** : Clear abrasion and weather resistant extra soft PVC.
- Reinforcement** : Blue PVC helix.
- Tube** : Smooth clear extra soft PVC.
- Temperature** : -40C to +65C(-40F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4	0.95	29	3.00	90	0.160	100	SATLT-075
1	1.24	29	3.00	85	0.260	100	SATLT-100
1 1/4	1.54	29	4.00	80	0.340	100	SATLT-125
1 1/2	1.81	29	5.00	70	0.440	100	SATLT-150
2	2.39	29	7.00	70	0.750	100	SATLT-200
2 1/2	2.94	29	8.00	70	1.020	100	SATLT-250
3	3.43	29	10.00	65	1.210	100	SATLT-300
4	4.54	29	14.00	50	2.020	100	SATLT-400
6	6.67	29	23.00	35	3.700	100	SATLT-600

Cut Lengths : Plus 10%

Standard Lengths : 100'

Safety Information : Suction and Pressure ratings are based on a temperature of 20C (68F), reduce by 50% at maximum working temperature

Recommended Couplings : Cam and groove or short shank