



# SATURN WHITE PVC WATER S&D



- Application** : An economical, flexible hose for construction pumps, septic tank & marine pump-out service. Resistant to some chemicals, mild acids & alkalis. Consult us for recommendations.
- Cover** : Clear abrasion and weather resistant PVC.
- Reinforcement** : White PVC helix.
- Tube** : Smooth clear PVC.
- Temperature** : -20C to +65C(-5F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4	0.95	29	2.00	90	0.160	100	SATW-075
1	1.18	29	3.00	85	0.190	100	SATW-100
1 1/4	1.47	29	3.00	80	0.290	100	SATW-125
1 1/2	1.72	29	4.00	70	0.350	100	SATW-150
2	2.29	29	5.00	65	0.570	100	SATW-200
2 1/2	2.85	29	6.00	60	0.870	100	SATW-250
3	3.35	29	8.00	55	1.030	100	SATW-300
4	4.45	29	10.00	50	1.780	100	SATW-400
6	6.67	29	25.00	35	3.700	100	SATW-600

**Cut Lengths** : Plus 10%

**Standard Lengths** : 100'

**Safety Information** : Suction and Pressure ratings are based on a temperature of 20C (68F), reduce by 50% at maximum working temperature

**Recommended Couplings** : Cam and groove or short shank