



SILICONE COOLANT HOSE



- Application** : Truck and bus fleets and other areas where long service life under high temperature conditions is required.
- Cover** : Blue heat and weather resistant silicone with wrapped impression finish.
- Reinforcement** : Multiple plies of polyester fabric.
- Tube** : Red heat resistant silicone.
- Temperature** : -54C to +177C(-65F to +350F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
3/8"	0.75"	110	0.20	12'	SILC-038
1/2"	0.88"	110	0.25	12'	SILC-050
5/8"	1.00"	110	0.30	12'	SILC-063
3/4"	1.13"	110	0.33	12'	SILC-075
7/8"	1.26"	110	0.40	12'	SILC-088
1"	1.38"	90	0.43	12'	SILC-100
1-1/16"	1.44"	90	0.45	12'	SILC-106
1-1/8"	1.51"	90	0.47	12'	SILC-113
1-1/4"	1.63"	85	0.53	12'	SILC-125
1-5/16"	1.69"	85	0.55	12'	SILC-131
1-3/8"	1.76"	85	0.58	12'	SILC-138
1-1/2"	1.88"	80	0.60	12'	SILC-150
1-5/8"	2.00"	80	0.60	12'	SILC-163
1-3/4"	2.13"	80	0.68	12'	SILC-175
1-7/8"	2.26"	80	0.68	12'	SILC-187
2"	2.38"	75	0.78	12'	SILC-200
2-1/8"	2.50"	75	0.87	12'	SILC-213
2-1/4"	2.63"	65	0.87	12'	SILC-225
2-3/8"	2.76"	65	0.90	12'	SILC-238
2-1/2"	2.88"	65	0.93	12'	SILC-250
2-5/8"	3.00"	60	1.00	12'	SILC-263
2-3/4"	3.13"	50	1.03	12'	SILC-275
3"	3.38"	50	1.13	12'	SILC-300
3-1/2"	3.88"	35	1.37	12'	SILC-350
4"	4.38"	35	1.53	12'	SILC-400
4-1/2"	4.88"	25	1.68	12'	SILC-450
5"	5.38"	25	1.88	12'	SILC-500
5-1/2"	5.88"	20	2.13	12'	SILC-550
6"	6.38"	20	2.20	12'	SILC-600

Cut Lengths : No Cut Lengths

Standard Lengths : 4'/12'

Recommended Couplings : Cam and groove, combination nipples