



STEAM 250



- Application** : An extremely flexible hose for use with saturated steam at pressures to 250 PSI .
- Cover** : Red abrasion and heat resistant EPDM rubber, with embossed brand and pressure.
- Reinforcement** : Multiple layers of high tensile steel cords.
- Tube** : Black heat resistant EPDM synthetic rubber.
- Temperature** : -40C to +210C(-40F to +406F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1/2"	0.98"	250	0.36	50'	ST250-050-50
1/2"	0.98"	250	0.36	100'	ST250-050-100
3/4"	1.26"	250	0.50	50'	ST250-075-50
3/4"	1.26"	250	0.50	100'	ST250-075-100
1"	1.50"	250	0.70	50'	ST250-100-50
1"	1.50"	250	0.70	100'	ST250-100-100
1-1/4"	1.81"	250	1.01	50'	ST250-125-50
1-1/4"	1.81"	250	1.01	100'	ST250-125-100
1-1/2"	2.13"	250	1.25	50'	ST250-150-50
1-1/2"	2.13"	250	1.25	100'	ST250-150-100
2"	2.64"	250	1.48	50'	ST250-200-50
2"	2.64"	250	1.48	100'	ST250-200-100
2-1/2"	3.22"	250	2.00	100'	ST250-250
3"	3.78"	250	3.40	100'	ST250-300

Cut Lengths : Plus 10%
Standard Lengths : 50'/100'
Recommended Couplings : High Pressure with interlocking clamps