



WHITE SANITARY



- Application** : For general clean-up and hot water washdown service in dairies, creameries, meat packing houses, food processing and bottling plants.
- Cover** : White heat and abrasion resistant EPDM synthetic rubber.
- Reinforcement** : Two layers of synthetic yarns, fungus and mould resistant.
- Tube** : Black heat resistant EPDM synthetic rubber.
- Temperature** : -40C to +93C(-40F to 200F)

| Nom. I.D | Nom. O.D | PSI | Weight (lbs) | Std Pack Qty | Part # |
|----------|----------|-----|--------------|--------------|---------|
| 1/2" | 0.91" | 250 | 0.31 | 700' | SAN-050 |
| 3/4" | 1.25" | 200 | 0.54 | 700' | SAN-075 |

Cut Lengths : Plus 10%
Standard Lengths : 50'/300' Coils/700' reels
Recommended Couplings : Long Shank or High pressure



JACKHAMMER - YELLOW AIR



- Application** : An economical air hose for jackhammer and other uses on construction sites. Also for general industrial use
- Cover** : Yellow smooth cut and abrasion resistant
- Reinforcement** : Multiple layers of synthetic yarn
- Tube** : Synthetic oil mist resistant
- Temperature** : -35C to +80C(-30F to +180F)

| Nom. I.D | Nom. O.D | PSI | Weight (lbs) | Std Pack Qty | Part # |
|----------|----------|-----|--------------|--------------|-------------|
| 3/4" | 1.14" | 300 | 0.43 | 300' | JACK-075 |
| 3/4" | 1.14" | 300 | 0.43 | 50' | JACK-075-50 |

Cut Lengths : Plus 5%

Standard Lengths : 50'/300' coils

Recommended Couplings : High Pressure, mine stem and nut, Universal quick acting



CONTRACTORS AIR



- Application** : For mining, construction, and industrial use
- Cover** : Yellow cut and abrasion resistant rubber
- Reinforcement** : Multiple layers of synthetic yarn
- Tube** : Synthetic oil mist resistant
- Temperature** : -35C to +80C(-30F to +180F)

| Nom. I.D | Nom. O.D | PSI | Weight (lbs) | Std Pack Qty | Part # |
|----------|----------|-----|--------------|--------------|-------------|
| 1/2" | 0.91" | 300 | 0.32 | 50' | CAY-050-50 |
| 1/2" | 0.91" | 300 | 0.32 | 100' | CAY-050-100 |
| 3/4" | 1.18" | 300 | 0.48 | 50' | CAY-075-50 |
| 3/4" | 1.18" | 300 | 0.48 | 100' | CAY-075-100 |
| 1" | 1.50" | 300 | 0.70 | 50' | CAY-100-50 |
| 1" | 1.50" | 300 | 0.70 | 100' | CAY-100-100 |
| 1-1/4" | 1.69" | 300 | 0.73 | 50' | CAY-125-50 |
| 1-1/4" | 1.69" | 300 | 0.73 | 100' | CAY-125-100 |
| 1-1/2" | 1.97" | 300 | 0.93 | 50' | CAY-150-50 |
| 1-1/2" | 1.97" | 300 | 0.93 | 100' | CAY-150-100 |
| 2" | 2.60" | 300 | 1.56 | 50' | CAY-200-50 |
| 2" | 2.60" | 300 | 1.56 | 100' | CAY-200-100 |
| 2-1/2" | 3.03" | 250 | 1.67 | 100' | CAY-250 |
| 3" | 3.66" | 250 | 2.00 | 100' | CAY-300 |
| 4" | 4.68" | 250 | 2.71 | 100' | CAY-400 |

Cut Lengths : Plus 10%

Standard Lengths : 50'/100'

Recommended Couplings : High Pressure all sizes, mine stem and nut 1/2" - 2", Universal quick acting 1/2" - 1"



REINFORCED CLEAR PVC



- Application** : An economical hose for handling air, water, oil, mild chemicals, and alkalis. Clear wall allows visual inspection of product.
- Cover** : Clear smooth PVC
- Reinforcement** : Multiple layers of synthetic yarns
- Temperature** : -5C to +65C(+25F to +150F)

| Nom. I.D | Nom. O.D | PSI | Weight (lbs) | Std Pack Qty | Part # |
|----------|----------|-----|--------------|--------------|-----------|
| 3/16" | 0.38" | 250 | 0.05 | 300' | RCPVC-019 |
| 1/4" | 0.46" | 250 | 0.07 | 300' | RCPVC-025 |
| 5/16" | 0.53" | 250 | 0.08 | 300' | RCPVC-031 |
| 3/8" | 0.60" | 250 | 0.09 | 300' | RCPVC-038 |
| 1/2" | 0.75" | 200 | 0.15 | 300' | RCPVC-050 |
| 5/8" | 0.88" | 200 | 0.17 | 300' | RCPVC-063 |
| 3/4" | 1.03" | 150 | 0.23 | 300' | RCPVC-075 |
| 1" | 1.31" | 125 | 0.32 | 300' | RCPVC-100 |
| 1-1/4" | 1.69" | 100 | 0.58 | 300' | RCPVC-125 |
| 1-1/2" | 1.94" | 100 | 0.69 | 300' | RCPVC-150 |
| 2" | 2.50" | 75 | 1.00 | 300' | RCPVC-200 |

Cut Lengths : Plus 10%

Standard Lengths : 3/16"-3/4" 300' coil, 1" 200' coil, 1-1/4"-2" 100' coil

Recommended Couplings : Combination nipples, short shank, brass barbed, cam and groove



STEAM 250 CHLOROBUTYL



- Application** : An extremely flexible hose for use with saturated steam at pressures to 250 PSI .
- Cover** : Red abrasion and heat resistant EPDM synthetic rubber.
- Reinforcement** : One wire braid.
- Tube** : Black heat resistant Chlorobutyl synthetic rubber.
- Temperature** : -40C to +210C(-40F to +406F)

| Nom. I.D | Nom. O.D | PSI | Weight (lbs) | Std Pack Qty | Part # |
|----------|----------|-----|--------------|--------------|-------------|
| 1/2" | 1.00" | 250 | 0.40 | 50' | ST250CB-050 |
| 3/4" | 1.31" | 250 | 0.48 | 50' | ST250CB-075 |
| 1" | 1.56" | 250 | 0.59 | 50' | ST250CB-100 |
| 1-1/4" | 1.85" | 250 | 0.78 | 50' | ST250CB-125 |
| 1-1/2" | 2.13" | 250 | 1.07 | 50' | ST250CB-150 |
| 2" | 2.69" | 250 | 1.58 | 50' | ST250CB-200 |

Cut Lengths : No Cut Lengths

Standard Lengths : 50'

Recommended Couplings : High Pressure with interlocking clamps



PETROLEUM DISCHARGE 250



- Application** : For handling a wide range of petroleum products, including gasoline, as well as a number of chemical solutions.
- Cover** : Black, heat, oil and weather resistant Neoprene.
- Reinforcement** : Multiple layers of synthetic textile cords, with static wire.
- Tube** : Black, heat and oil resistant synthetic rubber.
- Temperature** : -35C to +88C(-30F to +190F)

| Nom. I.D | Nom. O.D | PSI | Weight (lbs) | Std Pack Qty | Part # |
|----------|----------|-----|--------------|--------------|------------|
| 2" | 2.50" | 250 | 1.14 | 100' | PDB250-200 |
| 2-1/2" | 3.03" | 250 | 1.48 | 100' | PDB250-250 |
| 3" | 3.54" | 250 | 1.80 | 100' | PDB250-300 |
| 4" | 4.64" | 250 | 2.81 | 100' | PDB250-400 |
| 6" | 6.69" | 250 | 5.20 | 100' | PDB250-600 |

Cut Lengths : Plus 10%

Standard Lengths : 50'/100'

Recommended Couplings : Cam and groove



PAINT SPRAY



- Application** : For use with low pressure spray guns, and agricultural chemicals. Suitable for conveying the following solvents. Acetone, alcohols, Butyl Cellosolve, Ethyl Acetate, M.E.K., M.I.B.K.,
- Cover** : Black weather, oil and chemical resistant thermoplastic rubber.
- Reinforcement** : Multiple layers of synthetic yarns.
- Tube** : Polyethylene for good solvent and chemical resistance.
- Temperature** : -40C to +52C(-40F to +125F)

| Nom. I.D | Nom. O.D | PSI | Weight (lbs) | Std Pack Qty | Part # |
|----------|----------|-----|--------------|--------------|---------------|
| 1/4" | 0.50" | 175 | 0.07 | 500' | PAINT-025-175 |
| 3/8" | 0.68" | 175 | 0.12 | 500' | PAINT-038-175 |
| 1/2" | 0.88" | 175 | 0.19 | 500' | PAINT-050-175 |

Cut Lengths : Plus 10%
Standard Lengths : 500' reels
Recommended Couplings : Crimp on, combination nipples