



STEELFLEX AIR



- Application** : High pressure air service for mining, construction and industrial use. More resistant to external abuse than textile air hose. Mandrel built
- Cover** : Yellow cut and abrasion resistant rubber with red stripe
- Reinforcement** : Multiple layers of high tensile steel cords
- Tube** : Synthetic oil mist resistant
- Temperature** : -35C to +80C(-30F to +180F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1/2"	0.98"	1000	0.37	50'	SFY-050-50
1/2"	0.98"	1000	0.37	100'	SFY-050-100
3/4"	1.26"	800	0.49	50'	SFY-075-50
3/4"	1.26"	800	0.49	100'	SFY-075-100
1"	1.50"	800	0.66	50'	SFY-100-50
1"	1.50"	800	0.66	100'	SFY-100-100
1-1/4"	1.77"	600	0.80	50'	SFY-125-50
1-1/4"	1.77"	600	0.80	100'	SFY-125-100
1-1/2"	2.09"	600	1.03	50'	SFY-150-50
1-1/2"	2.09"	600	1.03	100'	SFY-150-100
2"	2.60"	600	1.51	50'	SFY-200-50
2"	2.60"	600	1.51	100'	SFY-200-100
2-1/2"	3.15"	500	2.12	100'	SFY-250
3"	3.82"	500	3.06	50'	SFY-300-50
3"	3.82"	500	3.06	100'	SFY-300-100
4"	4.84"	400	4.07	100'	SFY-400

Cut Lengths : Plus 10%, No cut lengths on 4".
Standard Lengths : 50'/100'
Recommended Couplings : High Pressure all sizes, mine stem and nut 1/2" - 2", Universal quick acting 1/2" - 1"