



SUPER WIREVAC (FOOD QUALITY)



Application : An extremely flexible transparent hose for use where full vacuum performance and higher working pressures are required while monitoring the contents of the hose. Ideal for use with most foodstuffs, cosmetics, beverages, and a wide range of chemical solutions. Also suitable for lubricating oils and animal fats.

Cover : Smooth clear PVC

Reinforcement : Spring steel wire helix and plies of polyester yarn

Tube : Smooth clear PVC

Temperature : -10C to +65C(15F to +150F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty	Part #
3/8"	0.73"	28"	1.20"	250	0.18	100'	WIRES-038
1/2"	0.81"	28"	1.50"	250	0.20	100'	WIRES-050
5/8"	0.98"	28"	2.00"	250	0.25	100'	WIRES-063
3/4"	1.17"	28"	2.40"	200	0.34	100'	WIRES-075
1"	1.38"	28"	3.00"	200	0.44	100'	WIRES-100
1-1/4"	1.69"	28"	3.70"	150	0.60	100'	WIRES-125
1-1/2"	1.97"	28"	4.50"	150	0.78	100'	WIRES-150
2"	2.50"	28"	5.50"	150	1.20	100'	WIRES-200
3"	3.55"	28"	13.00"	100	2.15	100'	WIRES-300

Safety Information : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature

Cut Lengths : Plus 10%

Standard Lengths : 100'