



TAN BULKMASTER



- Application** : Suction and discharge of non-oily, wet and dry abrasive materials such as corn, flour, sand, limestone powder, plastic pellets and sugar.
- Cover** : Tan non-marking, weather resistant EPDM, corrugated for flexibility.
- Reinforcement** : A high tensile steel helix embedded between layers of textile cords.
- Tube** : Tan smooth abrasion resistant, 3/16" FDA approved natural rubber.
- Temperature** : -32C to +80C(-25F to +180F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty	Part #
2"	2.72"	29"	7.00"	65	1.54	100'	TBT-200
2-1/2"	3.19"	29"	8.00"	65	1.84	100'	TBT-250
3"	3.70"	29"	10.00"	65	2.17	100'	TBT-300
4"	4.76"	29"	14.00"	50	3.33	100'	TBT-400
5"	5.79"	29"	20.00"	50	3.94	100'	TBT-500
6"	6.77"	29"	24.00"	50	5.25	100'	TBT-600
8"	8.97"	29"	30.00"	50	8.72	100'	TBT-800

Cut Lengths : Plus 10%
Standard Lengths : 100'
Recommended Couplings : Cam and groove