



## VITON LINED DISCHARGE



- Application** : For use with extremely corrosive chemicals, highly aromatic fuels, and petroleum based oils at elevated temperature. Contact us for recommendations
- Cover** : Orange chemical and abrasion resistant nitrile rubber with black identification stripe.
- Reinforcement** : Multiple layers of synthetic yarn
- Tube** : Black fuel and chemical resistant Viton.
- Temperature** : -32C to +121C(-25F to +250F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1/2"	0.95"	150	0.33	100'	VLD-050
3/4"	1.22"	150	0.45	100'	VLD-075
1"	1.48"	150	0.56	100'	VLD-100
1-1/2"	2.00"	150	0.88	100'	VLD-150
2"	2.60"	150	1.30	100'	VLD-200
3"	3.60"	150	2.20	100'	VLD-300

**Cut Lengths** : Plus 10%  
**Standard Lengths** : 100'  
**Recommended Couplings** : Cam and groove

## VITON LINED SUCTION



- Application** : For use with extremely corrosive chemicals, highly aromatic fuels, and petroleum based oils at elevated temperature. Contact us for recommendations
- Cover** : Orange chemical and abrasion resistant nitrile rubber with black identification stripe.
- Reinforcement** : High tensile steel wire helix embedded between layers of synthetic yarns.
- Tube** : Black fuel and chemical resistant Viton.
- Temperature** : -32C to +121C(-25F to +250F)

Nom. I.D	Nom. O.D	Vacuum (Hg)	Bend Radius	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4"	1.15"	28"	4.50"	150	0.50	100'	VLS-075
1"	1.40"	28"	5.00"	150	0.60	100'	VLS-100
1-1/2"	2.00"	28"	6.00"	150	0.95	100'	VLS-150
2"	2.60"	28"	7.00"	150	1.48	100'	VLS-200
3"	3.60"	28"	12.00"	150	2.20	100'	VLS-300

**Cut Lengths** : Plus 10%  
**Standard Lengths** : 100'  
**Recommended Couplings** : Cam and groove