




WIREVAC (FOOD GRADE)



- Application** : An extremely flexible transparent hose for use where full vacuum performance is required while monitoring the contents of the hose. Ideal for use with most foodstuffs, cosmetics, beverages, and a wide range of chemical solutions. Also suitable for lubricating oils and animal fats.
- Cover** : Smooth clear PVC
- Reinforcement** : Spring steel wire helix
- Tube** : Smooth clear PVC
- Temperature** : -10C to +65C(15F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
3/8	0.59	28	1.00	250	0.110	300	WIRE-038
1/2	0.71	28	1.50	250	0.120	300	WIRE-050
5/8	0.87	28	2.00	200	0.170	200	WIRE-063
3/4	1.02	28	2.00	180	0.240	200	WIRE-075
1	1.30	28	3.00	150	0.350	100	WIRE-100
1 1/4	1.61	28	3.50	100	0.500	100	WIRE-125
1 1/2	1.89	28	4.00	85	0.750	100	WIRE-150
2	2.44	28	5.00	65	1.090	100	WIRE-200
3	3.50	28	12.00	45	1.840	100	WIRE-300

Cut Lengths : Plus 10%

Standard Lengths : 100'

Product Information : Compliant with the applicable requirements and standards of FDA USDA and 3-A

Safety Information : Suction and pressure ratings are based on a temperature of 20C (68F), reduce ratings by 50% at maximum working temperature. This hose has no fabric reinforcement and normally should not be used under pressure for service at temperatures above 25C (75